

## REVISIONS TO CLAIMS

1. (previously presented) An optical wavefront modifier for modifying a wavefront of an optical beam passing through the modifier, the modifier comprising a first and a second transparent electrode layer and a medium for modifying the wavefront in dependence on electrical excitation of the medium and arranged between the electrode layers, the first electrode layer comprising three or more electrodes of a transparent, conductive material, characterized in that the first electrode layer comprises a series arrangement of resistors, the electrodes being electrically connected to the series arrangement of resistors and the resistors being made of said transparent, conductive material wherein the series arrangement of resistors is integrated in the electrodes.

2. (previously presented) Optical wavefront modifier according to Claim 1, wherein at least the first electrode layer comprises three terminals, which are electrically connected to the series arrangement of resistors.

3. (original) Optical wavefront modifier according to Claim 1, wherein the electrodes have a configuration for imparting a wavefront modification in Seidel form.

4. (cancelled)

5. (previously presented) A device for scanning an optical record carrier having a transparent layer and an information layer, comprising a radiation source for generating a radiation beam, an objective system for converging the radiation beam through the transparent

C:\My Documents\Aurac\legal practice\philips\prosecution\17843 - sup.doc

2

# REVISIONS TO CLAIMS

4 layer to a focus on the information layer, and a detection system for intercepting radiation from  
5 the record carrier, characterized in that an optical wavefront modifier according to claim 1 is  
6 arranged in the optical path between the radiation source and the detection system.

6. (previously presented) A device for scanning an optical record carrier having a transparent  
layer and an information layer, comprising a radiation source for generating a radiation beam, an  
objective system for converging the radiation beam through the transparent layer to a focus on  
the information layer, and a detection system for intercepting radiation from the record carrier,  
characterized in that an optical wavefront modifier according to claim 2 is arranged in the optical  
path between the radiation source and the detection system.

7. (previously presented) A device for scanning an optical record carrier having a transparent  
layer and an information layer, comprising a radiation source for generating a radiation beam, an  
objective system for converging the radiation beam through the transparent layer to a focus on  
the information layer, and a detection system for intercepting radiation from the record carrier,  
characterized in that an optical wavefront modifier according to claim 3 is arranged in the optical  
path between the radiation source and the detection system.

8. (currently amended) A wavefront modifier arranged to receive and modify an incident  
radiation beam, the modifier comprising:  
▪ at least a first and a second transparent electrode layer, at least the first electrode layer  
comprising three or more electrodes of a transparent, conductive material, the electrodes  
defining a first center of symmetry, the first layer being positioned so that the first center of

## REVISIONS TO CLAIMS

6 symmetry is displaced from an optical center of the radiation beam in a first displacement  
7 direction; and

- 8
  - at least one ~~a~~-medium for modifying the wavefront in dependence on electrical excitation of
- 9 ~~the medium and arranged between the electrode layers.~~

10. (previously presented) The modifier of claim 8 wherein the second layer has a configuration  
substantially identical to the first electrode layer, and defining a second center of symmetry, said  
second center of symmetry being displaced from the optical center of the radiation beam  
according to a second displacement direction, which second displacement direction is different  
from the first displacement direction.

10. (currently amended) A device for scanning an optical record carrier having a transparent  
layer and an information layer, comprising

- a radiation source for generating the radiation beam,
- an objective system for converging the radiation beam through the transparent layer to a focus  
on the information layer, and
- a detection system for intercepting radiation from the record carrier,
- an optical wavefront modifier according to claim 8 arranged in the optical path between the  
radiation source and the detection system, wherein the first direction of displacement is  
chosen to compensate for an expected motion of the ~~optical record carrier~~ objective lens  
system during playoperation.